



LEXCOR MATERIAL SAFETY DATA SHEET

DATE PREPARED: 04/20/2015

SECTION 1 - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME

ROOFMAX MAGIC SAND

SUPPLIER NAME AND ADDRESS

Lexsco 2010 Corporation
3275 Orlando Dr.
Mississauga, ON L4V 1C5
Tel: 905.792.8300 Fax: 905.792.8305

EMERGENCY TELEPHONE NUMBER:

CANUTEC 613-996-6666 (24 hours every day)

Description: Light Gray Clay Granules

SECTION 2 - HEALTH HAZARD DATA

Inhalation of dust may irritate nose and throat.

Always remember to wash hands thoroughly after handling this product.

No medical conditions are known to be aggravated by exposure to this product.

First Aid

Inhalation: Remove to fresh air. If breathing problems develop, call a doctor.
Eye Contact: Flush eyes with plenty of water for 15 minutes. If irritation persists, call a doctor.
Skin Contact: Wash skin with water.
Ingestion: Drink a glassful of water. Call a doctor or poison control centre.

SECTION 3 - HAZARDOUS INGREDIENTS

Ingredient Name	CAS #	Concentration	Worker Exposure Limit
Bentonite Clay	1302-78-9	≥ 80%	Not established.
Calcium Carbonate	1317-65-3	≤ 20%	10 mg/m ³ – TLV-TWA ^a (total dust) 15mg/m ³ – PEL-TWAb (total dust) 5mg/m ³ – PEL TWAb (respirable dust)
Crystalline Silica (Quartz)	14808-60-7	1-4%	0.05 mg/m ³ – TLV-TWA ^a (respirable dust)

^aTLV-TWA = ACGIH Threshold Limit Value – Time Weighted Average
^bPEL-TWA = OSHA Permissible Exposure Limit – Time Weighted Average

IARC Monographs (Volume 68, 1997) state that there is sufficient evidence of the carcinogenicity of inhaled crystalline silica (quartz) from occupational sources in humans. IARC classification – Group 1.

None of the other materials in this product are on the IARC, OSHA, or NTP carcinogen lists.

SECTION 4 - SPECIAL PROTECTION AND PRECAUTIONS

Hygienic Practices:	Wash hands after direct contact.
Engineering Controls:	Use general ventilation to minimize exposure to dust.
Personal Protective Equipment:	In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.

Particles may scratch hard surfaces, such as vinyl flooring.

Do not use this product as a traction aid because product becomes slippery and slick when wet.

SECTION 5 - TRANSPORTATION AND REGULATORY DATA

DOT/IATA/IMDG:	Not restricted.
EPA – SARA Title III/CERCLA:	This product is regulated under Sections 311/312. This product contains no chemicals regulated under Section 313 or under Section 304/CERCLA.

SECTION 6 - SPILL PROCEDURES/WASTE DISPOSAL

Spill Procedures:	Vacuum sweep, if possible, to avoid generating airborne dust. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material.
-------------------	---

Waste Disposal:	Reclaim, if possible, since material may be used as an absorbent for liquid spills. Otherwise, dispose of in accordance with all applicable federal, state, and local regulations.
-----------------	--

SECTION 7 - REACTIVITY DATA

Stable under normal use and storage conditions.

SECTION 8 - FIRE AND EXPLOSION DATA

Not flammable or explosive.

SECTION 9 - PHYSICAL DATA

Bulk density (g/cm ³):	~1.1
Solubility in water:	Insoluble

SECTION 10 - OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Reference: *The information herein is presented in good faith and believed to be correct as of the date hereof. Information is based upon supplier issued material safety data sheets and may be subject to error. If apprised of changes, updated MSDS will be promptly issued. Users must make their own determination regarding the suitability of the product for their own purposes prior to use.*

Prepared by Lexsuco 2010 Corporation.