



# LEXCOR MATERIAL SAFETY DATA SHEET

DATE PREPARED: 08/03/2015

NOTE: Under Government regulations, a MSDS is not required for this product; it is an end use product.

## SECTION 1 - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

### PRODUCT NAME

NO. 15 PERFORATED ROOFING FELT

### SUPPLIER NAME AND ADDRESS

*Lexusco 2010 Corporation  
3275 Orlando Dr.  
Mississauga, Ontario L4V 1C5  
Tel: 905.792.8300 Fax: 905.792.8305*

### EMERGENCY TELEPHONE NUMBER:

*CANUTEC 613-996-6666 (24 hours every day)*

**Chemical Formula:** Asphalt on a cellulose fiber sheet.  
**General Use:** Roofing Felt.

## SECTION 2 - HAZARDOUS INGREDIENTS

This material contains no hazardous materials. Asphalt on/in a cellulose fiber sheet.

## SECTION 3 - PHYSICAL DATA

Boiling Point: Not applicable.  
Specific Gravity: Not applicable.  
Vapour Pressure: Not applicable.  
Evaporation Rate: Not applicable.  
Appearance: Black Felt.  
Odour: Slight petroleum odour.

## SECTION 4 - FIRE AND EXPLOSION DATA

Flash Point: Not applicable.  
Flammable Limits: Not applicable.  
Extinguishing Media: Dry chemical, carbon dioxide, water.  
Special Procedures: Respirators required for fire fighting.

## SECTION 5 - TOXICOLOGICAL PROPERTIES

Exposure Limits: Not applicable.  
Primary Route of Exposure: Not applicable.  
Exposure Effects: Not applicable.

**WARNING:** This product may contain oxidized bitumens. The International Agency for Research on Cancer (the "IARC") published a monograph in 2013 which concluded that "occupational exposure to oxidized bitumens and their emissions during roofing operations are probably carcinogenic to humans." The IARC found that there is "limited evidence" in humans for the carcinogenicity of occupational exposures to bitumens and bitumen emissions during roofing and mastic-asphalt work. The IARC also found that there is "sufficient evidence" in experimental animals for carcinogenicity of fume condensates generated from oxidized bitumen. All other evidence of cancer in humans and experimental animals was judged "inadequate" or "limited." The physical nature of this product may help limit any inhalation hazard from oxidized asphalt during application in its hardened state. However, physical forces such as grinding, drilling and other demolition work on this product may liberate dust containing oxidized asphalt. Burning or heating of the product may cause fumes, vapours or mists.

## SECTION 6 - REACTIVITY DATA

Stability:	Stable
Polymerization:	Will not occur
Materials to Avoid:	Not applicable
Hazardous Decomposition Products:	Not applicable

## SECTION 7 - PREVENTATIVE MEASURES

Spill Procedure:	Not applicable
Disposal Procedure:	Standard waste disposal
Ventilation:	Not applicable
Respiratory:	Not applicable
Gloves:	Not applicable
Eye Protection:	Not applicable
Other:	Not applicable

## SECTION 8 - FIRST AID PROCEDURES

Not applicable.

## SECTION 9 - OTHER INFORMATION

*The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.*

**Reference:** *The information herein is presented in good faith and believed to be correct as of the date hereof. Information is based upon supplier issued material safety data sheets and may be subject to error. If apprised of changes, updated MSDS will be promptly issued. Users must make their own determination regarding the suitability of the product for their own purposes prior to use.*

*Prepared by Lexsuco 2010 Corporation.*