



LEXCOR SAFETY DATA SHEET

DATE PREPARED: 08/03/2015

SECTION 1 - PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME

LEXCOR VANGUARD 95FS, 180FS, 180 SS, 180SA, & 250 MOPPED CAP

SUPPLIER NAME AND ADDRESS

*Lexsuco Corporation
3275 Orlando Dr.
Mississauga, Ontario L4V 1C5
Tel: 905.792.8800 Fax: 905.792.8801*

EMERGENCY TELEPHONE NUMBER:

CANTEC: 613.996.6666

Chemical Name: Not Applicable
Trade Name: Modified Bitumen Roofing
Chemical Family: Not Applicable
Formula: Mixture of asphalt, polymers, inert mineral filler, surfacing and talc.

SECTION 2 - PREPARATION INFORMATION

Prepared/Reviewed by: Lexsuco Corporation
Phone Number: (905) 792 8800
Date: August 03, 2015

SECTION 3 - HAZARDOUS INGREDIENTS

Asphalt, traprock dust and/or calcium carbonate, fiberglass, polyester, plastic polymers, graphite and/or styrene rubbers. Contains no solvents or asbestos

SECTION 4 - PHYSICAL DATA

Boiling Point: Not applicable
Specific Gravity: > 1.0
Vapour Pressure: Not applicable
Evaporation Rate: Not applicable
Solubility in Water: Insoluble
Appearance: Various colours, sheet material
Odour: Slight petroleum odour

SECTION 5 - FIRE EXPLOSION HAZARD

Flash Point: Not applicable
Flammable Limits: Not applicable
Extinguishing Media: Dry chemical, carbon dioxide; water fog.
Special Procedures: Respirators required for firefighting.

SECTION 6 - TOXICOLOGICAL PROPERTIES

| | |
|-----------------------------------|--|
| Exposure Limits: | Not applicable |
| Primary Route of Exposure: | Skin contact |
| Exposure Effects: | Possible skin irritation and dermatitis. |

WARNING: This product may contain oxidized bitumens. The International Agency for Research on Cancer (the "IARC") published a monograph in 2013 which concluded that "occupational exposure to oxidized bitumens and their emissions during roofing operations are probably carcinogenic to humans." The IARC found that there is "limited evidence" in humans for the carcinogenicity of occupational exposures to bitumens and bitumen emissions during roofing and mastic-asphalt work. The IARC also found that there is "sufficient evidence" in experimental animals for carcinogenicity of fume condensates generated from oxidized bitumen. All other evidence of cancer in humans and experimental animals was judged "inadequate" or "limited." The physical nature of this product may help limit any inhalation hazard from oxidized asphalt during application in its hardened state. However, physical forces such as grinding, drilling and other demolition work on this product may liberate dust containing oxidized asphalt. Burning or heating of the product may cause fumes, vapors or mists.

SECTION 7 - REACTIVITY DATA

| | |
|--------------------------------|----------------------------|
| Stability: | Stable |
| Polymerization: | Will not occur |
| Materials to Avoid: | Strong oxidizers Hazardous |
| Decomposition Products: | CO ₂ , CO. |

SECTION 8 - PREVENTATIVE MEASURES

| | |
|----------------------------|--|
| Spill Procedure: | Normal housekeeping |
| Disposal Procedure: | Follow federal, provincial/state, and local laws and regulations. |
| Ventilation: | Not necessary |
| Respiratory: | Not necessary |
| Gloves: | Minimize skin contact. Use protective gloves when handling material. |
| Eye Protection: | Use safety glasses or goggles when necessary. |
| Other: | If contact is unavoidable, wear all necessary protective gear. |

SECTION 9 - FIRST AID MEASURES

Wash hands with soap after handling.

SECTION 10 - OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Reference: *The information herein is presented in good faith and believed to be correct as of the date hereof. Information is based upon supplier issued material safety data sheets and may be subject to error. If apprised of changes, updated MSDS will be promptly issued. Users must make their own determination regarding the suitability of the product for their own purposes prior to use.*

Prepared by Lexsuco 2010 Corporation.